

# Specifications

## General Specifications

Item	Specification
Gap between underside of the toe link rubber boot and the chassis bracket	12.0 mm (0.473 in)
Height/distance between centre of halfshaft and edge of the fender trim	462 mm (18.19 in)

## Torque Specifications

Description	Nm	lb-ft
* Stabilizer bar link nuts	175	129
Stabilizer bar clamp nuts	115	85
Front axle crossmember bolts	115	85
Shock absorber and spring assembly to lower arm bolt	300	221
Shock absorber top mounting nuts	63	46
* Shock absorber upper bush rebound plate nut	98	72
Heat shield bolts	10	7
* Upper arm and wheel knuckle nut	70	52
* Tie-rod end ball joint nut	70	52
Brake hose retaining bracket to wheel knuckle bolt	25	18
*+ Halfshaft retaining nut	350	258
Brake hose to upper arm bolt	22	16
Upper arm nuts and bolts	175	129
Radiator access panel bolts	10	7
Wheel hub bolts	115	85
Brake disc dust shield bolts	10	7
Lower arm bolts	275	203
Lower arm ball joint retaining nut	115	85
Lower arm front camber adjusting bolt	275	203
Lower arm rear castor adjusting bolts	275	203
Toe link inner ball joint retaining nut	133	98
Rear camber adjusting bolts	133	98
Track rod end locking nuts	53	39
Wheel speed sensor bolt	10	7
Axle carrier bushing bolt - M14	105	77
Axle carrier bracket bolts	80	59
Road wheel nuts	140	103

\* New nut/bolts must be installed + Stake nut on completion