

Published: Mar 1, 2005

## Specifications

### General Specifications

Item	Specification
Gap between underside of the toe link rubber boot and the integrated body frame bracket	15.0 mm (0.591 in)
Height between the center of the halfshaft end and the edge of the fender trim	463 mm (18.19 in)

### Torque Specifications

Description	Nm	lb-ft
** Toe link bolt	175	129
* Toe link inner ball joint retaining nut	133	98
* Stabilizer bar link nuts	115	85
Stabilizer bar clamp bolts	62	46
Body mount retaining bolts	133	83
Shock absorber to the lower suspension arm nut and bolt	300	221
Shock absorber to suspension turret nuts	63	46
Lower arm to wheel knuckle bolt	175	129
Lower arm bolts	275	203
*+ Halfshaft retaining nut	350	258
Upper arm to wheel knuckle nut	133	98
Upper arm front bolt	175	129
Upper arm rear bolt	275	203
Brake tube unions	18	13
Rear camber adjusting bolts	133	98
Wheel speed sensor	9	7
Brake disc dust shield bolts	9	7
Parking brake cable coupling	8	6
Road wheel nuts	140	103

\* New nut must be installed + Nut must be staked after tightening \*\* Bolts may be reinstalled a maximum of 4 times, the bolt head must be marked using a centre punch each time the bolt is refitted. When 4 centre punch marks are visible, a new, 'Patched' bolt must be installed.